



LAFORGE FRONT HITCH MODEL *HDS*



HDS pictured on Case-IH Magnum with optional pushbar, remote SCV receptacles and selector-valve for single- or double-acting hydraulics

LAFORGE is offering several models of front hitches and front PTOs, to fit older tractor models.



This brochure focuses on the modular **HDS front hitch** with 5500 Kg (12 100 lbs) lift capacity.

It is a proven and simple design. Only one moving part, in addition to the lift cylinders and the center link, makes it extremely reliable and long lasting.

Many productivity enhancing options are available:

Weight Frame, Remote SCV Outlets, Hydraulic Center Link, etc.



Optional Weight Frame



Technical data:

Front hitch HDS

- Category: 3N
- Lift capacity at hook points :5500Kg (12 100 lbs)
- Lift range: 720 mm (28.3")

PTO with multi-disc wet clutch and modulated engagement:

- 1000 RPM, clockwise rotation available for some tractor models.

The optional reinforcing **PUSHBAR** is strongly recommended for use with dozer blades as well as wide and heavy implements.

LAFORGE SARL
Pole d'Activit s
02190 GUIGNICOURT
(France)
Ph: 33 323 798 585
Fax: 33 323 798 175
commercial@laforge.fr
www.laforge.fr

LAFORGE SYSTEMS, INC
4425-C Treat Blvd, Suite 230
CONCORD - CA 94521
(USA)
Ph: (925) 827 2010 - 1 800 422 5636
Fax: (925) 689 7198
lars@fronthitch.com
www.fronthitch.com